





Technical Specification

Product Code: CL011

Description: 10AX 1 Gang 2 Way Plate Switch



General Information				
Dimensions (mm)	80 (W) x 80 (H) x 42 (D)			
Plate Fixing Centres - Horizontal (mm)	60.3			
MiniGrid Plate (Gang)	1			
MiniGrid Single Width Module Quantity	1			
MiniGrid Double Width Module Quantity	0			
Style	Metal Clad			
Finish	Metal Clad Grey			
Insert Colour	White (WH)			
Materials	Front Plate & Mounting Box: Electrophoretically Coated Steel		Insert & Rocker Switch: Urea	
	Rear Housing: Nylon		Terminals: Brass	
	Terminal Screws: Steel & Yellow Passivated		Contacts: Silver "on-lay" Copper / Brass	
	Internal Busbars: Formed Press	ed Brass	Earth Strap: Mild Ste	
Rated Voltage (V~) (Ue)	250		Frequency (Hz)	50
Inductive Load Rating (AX)	10			
Load Rating Comments	Suitable for Inductive Loads			
Termination Type	Screw			
Terminal Size (mm)	Ø3.5	Terminal	Torque Value (Nm)	0.5
Terminal Capacity - Solid (mm ²)	4 x 1.5 or 2 x 2.5			
Modular Rocker Switches	Yes			
2 Way Switch	Yes			
Supplied Back Box Depth (mm)	40			
Back Box Knockouts - Total (mm)	5 x Ø20			
Back Box Knockouts - Top (mm)	2 x Ø20 Back Box Knoc		kouts - Sides (mm)	1 x Ø20
Back Box Knockouts - Bottom (mm)	1 x Ø20 E	Back Box Kno	ckouts - Rear (mm)	None
Back Box Earth Terminal Supplied	Yes			
Operational Temperature (°C)	-5 to +40			
Warranty (Years)	10			
diagram Bare ear	ning / polishing of products, use c nat the mains supply is isolated by with the relevant product. th cables must always be covered agaphe with modules in the MiniG	efore comment	cing installation and re ate sleeving and wired	to the earth terminal.

CECK

Interchangeable with modules in the MiniGrid Range. Module colour to match is Click White (WH)

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com

Page 1 of 1 (18/02/22) Errors & Omissions excluded. Specification is subject to change without notice.