

Product Code: CL025

Description: 10AX 1 Gang Intermediate Plate Switch



**General Information**

<b>Dimensions (mm)</b>	80 (W) x 80 (H) x 42 (D)	
<b>Plate Fixing Centres - Horizontal (mm)</b>	60.3	
<b>MiniGrid Plate (Gang)</b>	1	
<b>MiniGrid Single Width Module Quantity</b>	1	
<b>MiniGrid Double Width Module Quantity</b>	0	
<b>Style</b>	Metal Clad	
<b>Finish</b>	Metal Clad Grey	
<b>Insert Colour</b>	White (WH)	
<b>Materials</b>	Front Plate & Mounting Box: Electrophoretically Coated Steel	Insert & Rocker Switch: Urea
	Rear Housing: Nylon	Terminals: Brass
	Terminal Screws: Steel & Yellow Passivated	Contacts: Silver "on-lay" Copper / Brass
	Internal Busbars: Formed Pressed Brass	Earth Strap: Mild Steel
<b>Rated Voltage (V~) (Ue)</b>	250	<b>Frequency (Hz)</b> 50
<b>Inductive Load Rating (AX)</b>	10	
<b>Load Rating Comments</b>	Suitable for Inductive Loads	
<b>Termination Type</b>	Screw	
<b>Terminal Size (mm)</b>	Ø3.5	<b>Terminal Torque Value (Nm)</b> 0.5
<b>Terminal Capacity - Solid (mm²)</b>	4 x 1.5 or 2 x 2.5	
<b>Modular Rocker Switches</b>	Yes	
<b>Intermediate Switch</b>	Yes	
<b>Supplied Back Box Depth (mm)</b>	40	
<b>Back Box Knockouts - Total (mm)</b>	5 x Ø20	
<b>Back Box Knockouts - Top (mm)</b>	2 x Ø20	
<b>Back Box Knockouts - Bottom (mm)</b>	1 x Ø20	
<b>Back Box Earth Terminal Supplied</b>	Yes	
<b>Operational Temperature (°C)</b>	-5 to +40	
<b>Warranty (Years)</b>	10	
<b>Back Box Knockouts - Sides (mm)</b>	1 x Ø20	
<b>Back Box Knockouts - Rear (mm)</b>	None	

**Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Interchangeable with modules in the MiniGrid Range. Module colour to match is Click White (WH)

