

Technical Specification



Product Code: CL036B

Description: 13A 2 Gang Double Pole Switched Socket Outlet



General Information		
Dimensions (mm)	140 (W) x 80 (H) x 42 (D)	
Plate Fixing Centres - Horizontal (mm)	120.6	
Style	Metal Clad	
Finish	Metal Clad Grey	
Materials	Front Plate & Mounting Box: Electrophoretically Coated Steel	Insert & Rocker Switch: Urea
	Rear Housing: Urea	Terminals: Brass
	Terminal Screws: Steel & Yellow Passivated	Contacts: Silver "on-lay" Copper / Brass
	Internal Busbars: Formed Pressed Brass	Earth Strap: Mild Steel
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Resistive Load Rating (A)	13	
Termination Type	Screw	
Terminal Size (mm)	Ø5 Termina	al Torque Value (Nm) 2
Terminal Capacity - Solid (mm ²)	3 x 2.5 or 2 x 4	
Double Pole Switch	Yes	
Twin Earth Terminals	Yes	
Supplied Back Box Depth (mm)	40	
Back Box Knockouts - Total (mm)	None	
Back Box Earth Terminal Supplied	Yes	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	
Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.		

UK