

Product Code: CMA146PL

Description: 1 Gang Unfurnished Dimmer Plate & Knobs (800W Max) - 2 Apertures



General Information

Plate Dimensions (mm)	86 (W) x 86 (H) x 9.5 (D)	
Plate Fixing Centres - Horizontal (mm)	60.3	
Style	Rounded Profile	
Finish	Polar White	
Materials	Front Plate & Control Button: Urea	Terminals: Brass
	Terminal Screws: Steel & Yellow Passivated	Earth Strap: Mild Steel
Anti Microbial Certified	Yes	
Termination Type	Screw	
Minimum Back Box Depth (mm)	25	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	20	

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
 All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.
 All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Compatible Dimmer Modules

- MD9014: 100W Dual Mode LED Dimmer Module
- MD9001: 6A Push ON/OFF (Dummy Dimmer / Non Dimmable) Module
- MD9010: 1-10V Analogue Rotary Dimmer Module
- MD9022: 40-250W Leading Edge Dimmer Module
- MD9042: 60-400W Leading Edge Dimmer Module

