

Technical Specification

Product Code: CMA404

Description: 2 Gang MiniGrid[®] Unfurnished Plate - 2 x 2 Apertures



General Information

| | |
|---|-----------------------------|
| Plate Dimensions (mm) | 146 (W) x 86 (H) x 9.5 (D) |
| Plate Fixing Centres - Horizontal (mm) | 120.6 |
| MiniGrid Plate (Gang) | 2 |
| MiniGrid Single Width Module Quantity | 2 x 2 |
| MiniGrid Double Width Module Quantity | 2 |
| Style | Rounded Profile |
| Finish | Polar White |
| Materials | Front Plate: Urea |
| Anti Microbial Certified | Yes |
| Modular Rocker Switches | Yes |
| Minimum Back Box Depth (mm) | Dependent On Modules Fitted |
| Ingress Protection | IP20 |
| Operational Temperature (°C) | -5 to +40 |
| Warranty (Years) | 20 |

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Interchangeable with modules in the MiniGrid Range. 