

# Technical Specification

Product Code: MD017PW

Description: 20A Flex Outlet Module



## General Information

<b>Dimensions (mm)</b>	25 (W) x 56.5 (H) x 30 (D)	
<b>Finish</b>	Polar White	
<b>Insert Colour</b>	Polar White	
<b>Materials</b>	Blank: Urea Terminals: Brass Bracket: Mild Steel Screws: Nickel Plated Steel	Rear Housing: Nylon Terminal Screws: Steel & Yellow Passivated Cord Grip: Nylon
<b>Rated Voltage (V~) (Ue)</b>	250	<b>Frequency (Hz)</b> 50
<b>Resistive Load Rating (A)</b>	20	
<b>Termination Type</b>	Screw	
<b>Terminal Size (mm)</b>	Ø3.5	<b>Terminal Torque Value (Nm)</b> 0.5
<b>Terminal Capacity - Solid (mm²)</b>	4 x 1.5 or 2 x 2.5	
<b>Modular Rocker Switches</b>	Yes	
<b>Flex Outlet Available</b>	Yes	
<b>Flex Outlet Location</b>	Front of Plate	<b>Flex Outlet Dimension (mm)</b> Ø10
<b>Minimum Back Box Depth (mm)</b>	25 (35 Flat Plate)	
<b>Operational Temperature (°C)</b>	-5 to +40	
<b>Warranty (Years)</b>	10	

**Additional Information** For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Suitable and matches the Definity, Mode, Polar & Part M ranges