

# Technical Specification

Product Code: MD022PW

Description: 20A Double Pole Switch Module



## General Information

<b>Dimensions (mm)</b>	41 (W) x 52.5 (H) x 22 (D)	
<b>Finish</b>	Polar White	
<b>Materials</b>	Rocker Switch: Urea	Rear Housing: Nylon
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated
	Contacts: Silver "on-lay" Copper / Brass	Internal Busbars: Formed Pressed Brass
<b>Anti Microbial Certified</b>	Yes	
<b>Rated Voltage (V~) (Ue)</b>	250	<b>Frequency (Hz)</b> 50
<b>Resistive Load Rating (A)</b>	20	
<b>Termination Type</b>	Screw	
<b>Terminal Size (mm)</b>	Ø4.4	<b>Terminal Torque Value (Nm)</b> 1.2
<b>Terminal Capacity - Solid (mm²)</b>	3 x 2.5 or 2 x 4	
<b>Modular Rocker Switches</b>	Yes	
<b>Double Pole Switch</b>	Yes	
<b>Minimum Back Box Depth (mm)</b>	25 (35 Flat Plate)	
<b>Operational Temperature (°C)</b>	-5 to +40	
<b>Warranty (Years)</b>	10	

**Additional Information** For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Suitable and matches the Definity, Mode, Polar & Part M ranges