

Technical Specification



oduct Code: MD047PW	Description: 13A Fused Con	nection Module
		ELICIT D.47 D.47 BS 9723 BA 250V- LIN LIN
General Information		
Dimensions (mm)	25 (W) x 57 (H) x 25.2 (D)	
Finish	Polar White	
Insert Colour	Polar White	
Materials	Cover & Fuse Drawer: Nylon	Rear Housing: Nylon
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated
	Internal Busbars: Formed Press	
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Resistive Load Rating (A)	13	
Fuse Fitted Rating & Type	13A (BS 1362)	
Termination Type		
Terminal Size (mm)		Terminal Torque Value (Nm) 0.5
Terminal Capacity - Solid (mm ²)	4 x 1.5 or 2 x 2.5	
Modular Rocker Switches	Yes	
Product Marking		
Minimum Back Box Depth (mm)	25 (35 Flat Plate)	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	
diagram	hat the mains supply is isolated b with the relevant product.	only a soft, dry, clean cloth. before commencing installation and refer to the circuit d with appropriate sleeving and wired to the earth terminal.
Suitable	and matches the Definity, Mode,	Polar & Part M ranges

UK

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com