

Product Code: OA036AG

Description: 2 Gang 13A DP IP66 Weatherproof Switched Socket Unit



General Information

Dimensions (mm)	158 (W) x 158 (H) x 90 (D)	
Accessory Fixing Centres (mm)	120.6	
Finish	Anthracite Grey	
Gasket Colour	Black	
Materials	Cover, Housing & Clip: Polycarbonate	Seal & Gasket: Rubber
	Accessory Plate & Housing: Urea	Terminals: Brass
	Terminal Screws: Steel & Yellow Passivated	Contacts: Silver "on-lay" Copper / Brass
	Internal Busbars: Formed Pressed Brass	Earth Strap: Mild Steel
Anti Microbial Certified	No	
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Resistive Load Rating (A)	13	
Termination Type	Screw	
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm) 2
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4	
Switched	Yes	
Double Pole Switch	Yes	
Twin Earth Terminals	Yes	
Back Box Knockouts - Total (mm)	8 x Ø20	Back Box Knockouts - Sides (mm) 2 x Ø20
Back Box Knockouts - Top (mm)	1 x Ø20	Back Box Knockouts - Rear (mm) 1 x Ø20
Back Box Knockouts - Bottom (mm)	2 x Ø20	
Ingress Protection	IP66	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	5	

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All grey & white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.