

Product Code: OA402AGU

Description: 2 Gang IP66 Weatherproof Unfurnished Switch Unit - MiniGrid



General Information

Dimensions (mm)	91 (W) x 106 (H) x 72.5 (D)		
Finish	Anthracite Grey		
Gasket Colour	Black		
Materials	Cover, Housing & Clip: Polycarbonate	Seal & Gasket: Rubber	
	Switch Membrane: Neoprene		
Anti Microbial Certified	No		
Modular Rocker Switches	Yes		
Back Box Knockouts - Total (mm)	5 x Ø20		
Back Box Knockouts - Top (mm)	1 x Ø20	Back Box Knockouts - Sides (mm)	1 x Ø20
Back Box Knockouts - Bottom (mm)	1 x Ø20	Back Box Knockouts - Rear (mm)	1 x Ø20
Ingress Protection	IP66		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	5		

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Interchangeable with 13A/10AX modules in the MiniGrid Range. **MINIGRID®**