

Product Code: PRC009

Description: 10AX 2 Way Pull Cord Switch



General Information

Dimensions (mm)	76 (Dia) x 51.5		
Style	Round		
Finish	Polar White		
Materials	Cover & Pattress: Urea Terminals: Brass Internal Busbars: Formed Pressed Brass Pull Bell: Urea	Terminal Housing: Urea Terminal Screws: Steel & Yellow Passivated Earth Strap: Mild Steel	
Anti Microbial Certified	Yes		
Rated Voltage (V~) (Ue)	250	Frequency (Hz)	50
Inductive Load Rating (AX)	10		
Load Rating Comments	Suitable for Inductive Loads		
Termination Type	Screw		
Terminal Size (mm)	Ø4	Terminal Torque Value (Nm)	0.4
Terminal Capacity - Solid (mm²)	2 x 1.5 or 1 x 2.5		
2 Way Switch	Yes		
Twin Earth Terminals	No		
Supplied Back Box Depth (mm)	Pattress Supplied		
Back Box Knockouts - Total (mm)	4 x 12 x 9 and 1 x 17 x 23		
Back Box Knockouts - Top (mm)	None	Back Box Knockouts - Sides (mm)	4 x 12 x 9
Back Box Knockouts - Bottom (mm)	None	Back Box Knockouts - Rear (mm)	1 x 17 x 23
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases. All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.