

**Product Code:** PRW213

**Description:** 50A Double Pole Round Pull Cord Switch With Mechanical 'On/Off', Neon & Pattress



### General Information

<b>Dimensions (mm)</b>	100 (Dia) x 77 (D)		
<b>Style</b>	Round		
<b>Finish</b>	Polar White		
<b>Materials</b>	Cover & Pattress: Urea Neon Lens: Polycarbonate Terminal Screws: Steel & Yellow Passivated Earth Strap: Mild Steel	Terminal Housing: Urea Terminals: Brass Internal Busbars: Formed Pressed Brass Pull Bell: Urea	
<b>Anti Microbial Certified</b>	Yes		
<b>Rated Voltage (V~) (Ue)</b>	250	<b>Frequency (Hz)</b>	50
<b>Resistive Load Rating (A)</b>	50		
<b>Termination Type</b>	Screw		
<b>Twin Screw Terminals</b>	Yes		
<b>Terminal Size (mm)</b>	Ø6.7	<b>Terminal Torque Value (Nm)</b>	2.5
<b>Terminal Capacity - Solid (mm²)</b>	1 x 25		
<b>Double Pole Switch</b>	Yes		
<b>Twin Earth Terminals</b>	No		
<b>Neon Indicator</b>	Yes	<b>Indicator Colour</b>	Orange
<b>Mechanical Indicator</b>	Yes		
<b>Mechanical Indicator Type</b>	Green Tab		
<b>Supplied Back Box Depth (mm)</b>	Pattress Supplied		
<b>Back Box Knockouts - Total (mm)</b>	2 x 16 x 8.5 or 23 x 12		
<b>Back Box Knockouts - Top (mm)</b>	None	<b>Back Box Knockouts - Sides (mm)</b>	2 x 23 x 12
<b>Back Box Knockouts - Bottom (mm)</b>	None	<b>Back Box Knockouts - Rear (mm)</b>	2 x 16 x 8.5
<b>Ingress Protection</b>	IP20		
<b>Operational Temperature (°C)</b>	-5 to +40		
<b>Warranty (Years)</b>	20		

### Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.