

**Product Code:** Q554.2

**Description:** Standard 3 Pin Time Switch, 2 on/off



### General Information

Dimensions	146.5mm x 105.7mm x 82mm
Display	24 Hour Dial
Wire Gauge	0.5 - 4mm <sup>2</sup>
Time Base	Quartz Crystal
Timing Accuracy	5 Minutes/Year

### Power

Operating Voltage	230VAC
Power Consumption	0.6W @ 230V
Power Reserve	100 Hours (Requires 300 hours to charge)
Battery Type	Rechargeable Ni-MH
IEC Protection Class	Class I (Must be earthed)
Live Parts Protection	Contained within the enclosure

### Construction

Base Type	3 Pin
Fixing	Surface Mounting

### Outputs

Contact Type	SPST
Total Switch Rating	20A, 230VAC
Maximum Current Rating (0.6pf Inductive)	5A
Maximum Current Rating (0.8pf Inductive)	12A
Halogen, Filament Lamp	3600W
Discharge (Sodium, Mercury, Metal Halide)	3600W
Fluorescent Lamp	1980W
LED 230VAC	3600W

### Programming

Programming Schedule	24 Hour Program
Day Omission	Yes (omits the "ON" operation)
Temporary Override Facility (Manual Button)	Advance to "OFF", when program "ON" and will remain "OFF" until next "ON" operation and vice versa
Dial Calibration	15 Minute Divisions
Setting Accuracy	+/- 3 Minutes
Available Operations	2 ON/OFF Periods

### Environment

Ingress Protection	IP20
Operating Temperature	0°C to 50°C

### Accessories

110469 FD930 Conduit Box Time Switch