

FUSED TIMER CONNECTION UNIT

Electronic - 7 Day

- + Ideal for control of:- towel rails, Panel heaters, immersion heaters & fan heaters
- + 4 'ON' & 'Off' settings per day
- + Large backlit LCD display
- + 12mm pattress supplied if extra spacing is needed
- + Will fit 25-47mm back boxes
- + '1 or 2 hour Boost' & 'Advance' controls
- + 700 hours battery life
- + Front cable entry
- + 1 year guarantee



T205

	T205
Description	Fused Timer Connection Unit 7 Day
Max Load	13A Resistive Load 6A Inductive Load
Product Finish	White
Barcode	5012739653964
Product Weight	188g
Product Dimensions	H86.5 x W86.5 x D40mm (D46.5mm including front switch)
Voltage	230V AC 50Hz
Rated Impulse Voltage	4,000V
Operating Temperature	-5°C to +40°C
Working Environment	Indoor use Only
Operation	Integrated Control
Battery Back Up	700 Hours
Display	Large Back Lit LCD
Pollution Degree	2
Manual Switch Type	Double Pole Switch
Timer Switch Type	Relay (single pole)
Settings	4 On & Off Settings per day
Cord Anchorage	Cable Dia: 4.6mm to 10.4mm
Terminal Capacity	Cable Size -3 x 1.0mm ² to 3 x 2.5mm ²
Guarantee	1 Year
Conforms To	BS 5733:2010+A1:2014, BS EN60730-1:2016+A1:2019, BS EN IEC 60730-2-7:2020 Fused Connection Unit Tests to: BS 1363-4:2016+A1:2018