

## **Technical Specification**



Output Relay Rating 16A Receiver Contact Rating (Volt

Free)

## Product Code: CHPRSTATDPRFS

Description: Choice Plus Wireless Digital Programmable Thermostat in Silver



Box)

140 x 88.6 x 32.1 (Without Back



## General Information Dimensions (mm)

Flush Mounting Back Box Depth (mm	<b>n)</b> 25
Finis	sh Silver
Call for Heat Indicatio	on LCD Display
Sensor Typ	Electronic Sensor for Accurate and Responsive Performance
Material	IS ABS
Transmission frequency (Mhz	z) 868
Transmission Distance	ce 80m Open Field 30m Indoor Transmission
Warranty (Years	rs) 3
Programming	
Programming Schedule	24 Hour or 7 Days
Adjustment Type	-
Set Temperature Range (°C)	5 to 35
TPI (Time Proportional & Integral) Control for Heating Efficiency	
Temperature Display Range (°C)	0 to 50
Temperature Swing Adjustment (°C)	
Optimisation	Optimum Start/ Delay Start and Optimum Stop for Additional Efficiency
Available Operations	Up to 6 per Day
Modes Available	
Pre-Programmed Schedule	Yes
Summer/Winter Time Change	Yes (Automatic)
Supply & Power	
Output Relay Ratir	ng 16A Receiver Contact Rating (Volt Free)
Battery Low Indicate	tor LCD Display (Transmitter)
Class Description	on TPI Room Thermostat, for use with ON/OFF Heaters, Value 2%
Environment	
Ingress Protection	IP30
	0 to +50
Frost Protection	Yes (5°C)
<b>Standards</b> BS EN 60730-1 BS EN 60730-2.9	

Unit 7 Target Park, Shawbank Road, Lakeside, Redditch B98 8YN United Kingdom **T:** +44 (0)1527 515150 | **F:** +44 (0)1527 515143 **E:** info@espuk.com | **W:** espuk.com



Page 1 of 1 (06/06/22) Errors & Omissions excluded. Specification is subject to change without notice.