essentials™

Insert & Rocker Switch: Urea

Contacts: Silver "on-lay" Copper / Brass

Terminals: Brass

Terminal Torque Value (Nm) 0.5

Earth Strap: Mild Steel

Frequency (Hz) 50

Technical Specification

Product Code: CL012B **Description:** 10AX 2 Gang 2 Way Plate Switch (No Knockouts)



General Information

Dimensions (mm) 80 (W) x 80 (H) x 42 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

MiniGrid Plate (Gang)

MiniGrid Single Width Module Quantity

MiniGrid Double Width Module Quantity

Style Metal Clad

Finish Metal Clad Grey

Insert Colour White (WH)

Materials Front Plate & Mounting Box:

Electrophoretically Coated Steel

Rear Housing: Nylon

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Rated Voltage (V~) (Ue) 250

Inductive Load Rating (AX) 10

Load Rating Comments Suitable for Inductive Loads

> Termination Type Screw

Terminal Size (mm)

Terminal Capacity - Solid (mm²) 4 x 1.5 or 2 x 2.5

> Modular Rocker Switches Yes

> > 2 Way Switch

Supplied Back Box Depth (mm)

Back Box Knockouts - Total (mm) None

Back Box Earth Terminal Supplied Yes

> Operational Temperature (°C) -5 to +40

Warranty (Years)

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Interchangeable with modules in the MiniGrid Range. Module colour to match is Click White (WH)

MINIGRID®

