## essentials™

Product Code: CL840

## **Technical Specification**

Description: 13A 2 Gang Double Pole Switched Socket Outlet With Outboard Rockers

& Neons



## **General Information**

**Dimensions (mm)** 140 (W) x 80 (H) x 42 (D)

Plate Fixing Centres - Horizontal (mm) 120.6

Style Metal Clad Finish Metal Clad Grey

Materials Front Plate & Mounting Box:

Electrophoretically Coated Steel

Rear Housing: Urea Neon Lens: Polycarbonate

Terminals: Brass Terminal Screws: Steel & Yellow Passivated

Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Insert: Urea

Earth Strap: Mild Steel

Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50

Resistive Load Rating (A) 13
Termination Type Screw

Terminal Size (mm) Ø5 Terminal Torque Value (Nm) 2

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Double Pole Switch Yes Twin Earth Terminals Yes

Neon Indicator Yes Indicator Colour Red

Supplied Back Box Depth (mm) 40 Back Box Knockouts - Total (mm)  $7 \times \emptyset 20$ 

Back Box Knockouts - Top (mm)3 x Ø20Back Box Knockouts - Sides (mm)1 x Ø20Back Box Knockouts - Bottom (mm)2 x Ø20Back Box Knockouts - Rear (mm)None

Back Box Earth Terminal Supplied Yes
Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

