


Technical Specification



Product Code: CMA840

Description: 13A 2 Gang Double Pole Switched Socket Outlet With Outboard Rockers & Neons





General Information

Plate Dimensions (mm) Plate Fixing Centres - Horizontal (mm) Style Finish Materials	146 (W) x 86 (H) x 9.5 (D) 120.6 Rounded Profile Polar White Front Plate & Rocker Switch: Urea Neon Lens: Polycarbonate Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass	Rear Housing : Urea Terminals: Brass Contacts: Silver "on Earth Strap: Mild Ste	-lay" Copper / Brass
Anti Microbial Certified	Yes		
Rated Voltage (V~) (Ue)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
Termination Type	Screw		_
Terminal Size (mm)	Ø5 Terminal Torque Value (Nm) 2		2
Terminal Capacity - Solid (mm ²)			
Double Pole Switch	Yes		
Twin Earth Terminals	Yes		0
Neon Indicator	Yes Indicator Colour Orange		
Minimum Back Box Depth (mm)	25		
Ingress Protection			
Operational Temperature (°C) Warranty (Years)	-5 to +40 20		
Ensure th diagram Bare ear All white propertie propertie All produ envelope	For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses. All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.		

UK CA