

JC50303

Emergency Exit Box

Exit Box Maintained 3M IP20 191X395mm 1800mAh including 1pcs Legend

Features & Benefits

- · Visible from a distance of 24 metres
- Supplied as standard with down running man legend
- Left/right or up running man legends bought separately
- · Top and rear conduit entry knock out points
- Suitable for use as maintained and non maintained









CLASSI

WARRANTY

General Information

Mounting

Environment

Suitable For Zones

Product Group

Product Range

Trade Name

Color Finish

Product Shape

Product Weight(kg)

Overall Dimensions

Light Source

Light Source Features

Additional Information

Luminaire Accessories

Recommended Product Location

Method Of Fix

Distance From Lighted Object

IP Rating

Warranty

Origin of manufacturer

Wall

Indoor

Outside zone 2

Emergency

Exit box

Emergency Range

White

Rectangular

1.46

390 x 190 x 60 mm

LED

Vibrant White

Viewing distance 36 metres

JC50304(Legend Left/Right) JC50314(Legend Up)

Wall mount, indoor use only

Screws and rawl plugs(not supplied)

0.3m

IP20

PRC

2 years standard warranty extends to 3 years when registered within the first year of purchase (2 years on

batteries) (See Website for terms and conditions)

Driver Manufacturer JCC

LED Manufacturer/Type SMD 2835/Epistar

Lighting Product Type 1 Emergency Lighting

Lighting Product Type 2 Surface Light

Electrical

Voltage Rating 220-240

Operating Frequency Hz 50Hz

Luminaire Circuit Wattage 5.7W(AC)8.6W(DC)

Class

S/L(brown), U/S live(black), Neutral(blue), Input Electrical Connections

Earth(yellow/green)

Battery Data

Battery Specification 3 cell AA Type Ni-Cd 3.6V 1500mAh

Battery run time 3hrs

Thermals

Operating Temperature Range °C 0 to +26

Performance Data

Hours life stated is an indication of expected L70 chip and light output calculations when operating in optimum conditions. Product warranty period supports the full product during the term given. The L70 hours expectancy is not correlated with the full product warranty term, nor is it a representation of lumen depreciation during the warranty period.

Actual Lumen Output 95 (AC) 48 (DC)

Lumens Per Circuit Watt 17 LpcW(AC) 6 LpcW(DC)

Correlated Color Temperature 7000K

Photometry Available No

Construction

Primary Material Steel

Packaging

Product Packaged Weight(kg) 1.56

Quantity Per Outer Carton 50


Product Bar Code EAN-13 Number 5052544047053

Standards & Approvals

Manufactured In Accordance To BS EN60598-2-22

CE Marked yes
UKCA Marked Yes
Date code/Purchase order No. Yes

Certificate Of Conformity Available on request







JCC Lighting LTD Innovation Centre, Beeding Close, Southern Cross Trading Estate, Bognor Regis, West Sussex PO22 9TS Sales: 01243 838999 (8am to 5pm Monday to Friday) Fax: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk | www.jcc.co.uk | www.jcc.co.uk | www.jcc.co.uk | www.jcc.co.uk | www.jcc.co.uk | www.jcc.co.uk | www.jc

This document is uncontrolled if printed, all information is subject to change

Version 71 [04/01/2022]