

NEW Available Jun 2020 **Erta**

5W LED fire rated downlight

- Integrated dimmable driver
- Push wire terminals
- Can be installed under Insulation layer
- Compact size

Add-on emergency **E+**

Modular design **ECO**



Satin Chrome

Order Code	Power	Beam Angle	Finish	Cut-out	CCT	Lumen	Trade Price
KFDL05DIM	5W	40°	White	55mm	3000K 4000K 6500K	450lm 470lm 500lm	£22.40
KFDL05DIM	5W	40°	Satin Chrome	55mm	3000K 4000K 6500K	450lm 470lm 500lm	£23.58

Optional Gear

Type	Order Code	Description	Trade Price
Emergency module	CEL03LIC/N	Three hour rated Li-Ion emergency module	£85.50

RF wireless triac dimmer

Order Code	Max Power	Output Current	Trade Price
CYDIMRFT1	2 x 120W (100 Vac) 2 x 288W (240 Vac)	2 x 1.2 A	£108.07

* See datasheet for recommended number of lamps per dimmer

- 3** 3 Years Standard Warranty
- 5** 5 Years Extended Warranty
- 1000V** Surge Protection (L to GND)
- Mains Dimmable** Dimmable
- 55mm** Cut-out
- 30/60/90 minutes** Fire rating



Recommended



Mains emergency P25 module

General Specification

Voltage	220-240Vac 50-60Hz
CRI	>82
Life Time	30,000h
Ambient Temp	-30°C to 40°C
Housing	Zinc coated sheet steel



Order Code

- KFDL05DIM/S30-WHT
- KFDL05DIM/S40-WHT
- KFDL05DIM/S65-WHT
- KFDL05DIM/S30-SCH
- KFDL05DIM/S40-SCH
- KFDL05DIM/S65-SCH

Dimensions

