

# Technical Specification

Product Code: MD017BKBN

Description: 20A Ingot Flex Outlet Module



## General Information

<b>Dimensions (mm)</b>	25 (W) x 56.5 (H) x 30 (D)	
<b>Finish</b>	Black Nickel	
<b>Insert Colour</b>	Black	
<b>Materials</b>	Blank: Urea Cover: Stainless Steel Terminal Screws: Steel & Yellow Passivated Cord Grip: Nylon	Rear Housing: Nylon Terminals: Brass Bracket: Mild Steel Screws: Nickel Plated Steel
<b>Rated Voltage (V~) (Ue)</b>	250	<b>Frequency (Hz)</b> 50
<b>Resistive Load Rating (A)</b>	20	
<b>Termination Type</b>	Screw	<b>Terminal Torque Value (Nm)</b> 0.5
<b>Terminal Size (mm)</b>	Ø3.5	
<b>Terminal Capacity - Solid (mm²)</b>	4 x 1.5 or 2 x 2.5	
<b>Modular Rocker Switches</b>	Yes	
<b>Flex Outlet Available</b>	Yes	
<b>Flex Outlet Location</b>	Front of Plate	<b>Flex Outlet Dimension (mm)</b> Ø10
<b>Minimum Back Box Depth (mm)</b>	25 (35 Flat Plate)	
<b>Operational Temperature (°C)</b>	-5 to +40	
<b>Warranty (Years)</b>	10	

**Additional Information** For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.