

Technical Specification



Product Code: MD022PW-CH Description: 20A Double Pole Switch Module COOKER Use of the second sec	Product Code: MD022PW-CH	Description: 201 Double Pole Swite	sh Madula	
HOOD Impose the product of the products, use only a soft, dry, clean clort. Exerct Information Impose the product of products, use only a soft, dry, clean clort. Dimensions (mm) 11 (W) × 52.5 (H) × 22 (D) Finish Polar Material Rocker Switch: Urea Rocker Switch: Urea Rear Housing: Nylon Contracts: Silver "on-lay" Copper / Brass Terminal Screws: Steel & Yellow Passivate Contracts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Anti Microbial Certifie Yes Rated Voltage (V~) (Ue) 20 Terminal Torque Value (Nm) 1.2 Terminal Size (mm) 94.4 Terminal Torque Value (Nm) 1.2 Terminal Size (mm) 94.5 or 2 × 4 Modular Rocker Switche Yes Product Marking Cocker Houd Yerduet Marking Cocker Houd Minimum Back Box Depth<(mm) 25 (S5 Flat Plate) Operational Temperature (*C) -5 to +40 Warranty (Years) 1		Description. ZuA Double Fole Switc	i module	
Dimensions (mm) 41 (W) × 52.5 (H) × 22 (D) Finish Polar White Materials Rocker Switch: Urea Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivate Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Anti Microbial Certified Yes Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50 Resistive Load Rating (A) 20 Terminal Size (mm) Ø4.4 Terminal Torque Value (Nm) 1.2 Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4 Modular Rocker Switches Yes Double Pole Switch Yes Yes Product Marking Cooker Hood Minimum Back Box Depth (mm) 25 (35 Flat Plate) Operational Temperature (°C) -5 to +40 Warranty (Years) 10 For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	HOOD		LIN 0227 023 2DA 250V- BS EN 80569 ES EN 80569 CLICX FOTT	
Finish Polar White Materials Rocker Switch: Urea Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivate Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Anti Microbial Certified Yes Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50 Resistive Load Rating (A) 20 Screw Screw Terminal Size (mm) Ø4.4 Terminal Torque Value (Nm) 1.2 Terminal Capacity - Solid (mm?) 3 x 2.5 or 2 x 4 Screw Screw Double Pole Switch Yes Scoker Hood Scoker Hood Minimum Back Box Depth (mm) 25 (35 Flat Plate) Scoker Hood Scoker Hood Minimum Back Box Depth (mm) 25 (35 Flat Plate) Scoker Hood Scoker Hood Modular Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.				
Materials Rocker Switch: Urea Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivate Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Anti Microbial Certified Yes Resistive Load Rating (A) 20 Resistive Load Rating (A) 20 Terminal Size (mm) Screw Terminal Capacity - Sold (mm) 3 x 2.5 or 2 x 4 Modular Rocker Switches Yes Yes Screw Conduct Rocker Switche Yes Yes Screw Terminal Capacity - Sold (mm) 3 x 2.5 or 2 x 4 Modular Rocker Switches Yes Yes <t< th=""><th></th><th></th><th></th></t<>				
Terminals: Brass Terminal Screws: Steel & Yellow Passivate Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Anti Microbial Certified Yes Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50 Resistive Load Rating (A) 20 Terminal Torpue Screw Terminal Size (mm) Ø4.4 Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4 Modular Rocker Switches Yes Product Marking Cooker Hood Minimum Back Box Depth (mm) 25 (35 Flat Plate) Operational Temperature (°C) -5 to +40 Warranty (Years) 10				
Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Anti Microbial Certified Yes Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50 Resistive Load Rating (A) 20 Screw </th <th>Materials</th> <th></th> <th></th>	Materials			
Anti Microbial CertifiedYesRated Voltage (V~) (Ue)250Frequency (Hz)50Resistive Load Rating (A)20Termination TypeScrewTerminal Size (mm)Ø4.4Terminal Torque Value (Nm)1.2Terminal Capacity - Solid (mm²)3 x 2.5 or 2 x 4Modular Rocker SwitchesYesDouble Pole SwitchYesProduct MarkingCooker HoodMinimum Back Box Depth (mm)25 (35 Flat Plate)Operational Temperature (°C)-5 to +40Warranty (Years)10Additional InformationFor clearing / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.				
Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50 Resistive Load Rating (A) 20 Termination Type Screw Terminal Size (m) Ø4.4 Terminal Torque Value (Nm) 1.2 Terminal Capacity - Solid (m²) 3 x 2.5 or 2 x 4 1.2 Modular Rocker Switche Yes Yes Double Pole Switch Yes Yes Product Marking Cooker Hood Yes Operational Temperature (°C) -5 to +40 Yes Warranty (Years) 10 10	Anti Microbial Cartified		s internal busbars. Formed Pressed brass	
Resistive Load Rating (A) 20 Termination Type Screw Terminal Size (mm) Ø4.4 Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4 Modular Rocker Switches Yes Double Pole Switch Yes Product Marking Cooker Hood Minimum Back Box Depth (mm) 25 (35 Flat Plate) Operational Temperature (°C) -5 to +40 Warranty (Years) 10			Frequency (Hz) 50	
Termination TypeScrewTerminal Size (mm)Ø4.4Terminal Torque Value (Nm)1.2Terminal Capacity - Solid (mm²) 3×2.5 or 2×4 Modular Rocker SwitchesYesDouble Pole SwitchYesProduct MarkingCooker HoodMinimum Back Box Depth (mm) $25 (35 Flat Plate)$ Operational Temperature (°C) -5 to $+40$ Warranty (Years)10Additional InformationFor cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.			riequency (nz) 50	
Terminal Size (mm)Ø4.4Terminal Torque Value (Nm)1.2Terminal Capacity - Solid (mm²)3 x 2.5 or 2 x 41.2Modular Rocker SwitchesYesDouble Pole SwitchYesProduct MarkingCooker HoodMinimum Back Box Depth (mm)25 (35 Flat Plate)Operational Temperature (°C)-5 to +40Warranty (Years)10Additional InformationFor cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.				
Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4 Modular Rocker Switches Yes Double Pole Switch Yes Product Marking Cooker Hood Minimum Back Box Depth (mm) 25 (35 Flat Plate) Operational Temperature (°C) -5 to +40 Warranty (Years) 10 Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.			erminal Torque Value (Nm) 1.2	
Modular Rocker Switches Yes Double Pole Switch Yes Product Marking Cooker Hood Minimum Back Box Depth (mm) 25 (35 Flat Plate) Operational Temperature (°C) -5 to +40 Warranty (Years) 10 Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.				
Product Marking Cooker Hood Minimum Back Box Depth (mm) 25 (35 Flat Plate) Operational Temperature (°C) -5 to +40 Warranty (Years) 10 Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	,			
Minimum Back Box Depth (mm) 25 (35 Flat Plate) Operational Temperature (°C) -5 to +40 Warranty (Years) 10 Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Double Pole Switch	Yes		
Operational Temperature (°C) -5 to +40 Warranty (Years) 10 Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Product Marking	Cooker Hood		
Warranty (Years)10Additional InformationFor cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Minimum Back Box Depth (mm)	25 (35 Flat Plate)		
Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Operational Temperature (°C)	-5 to +40		
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Warranty (Years)	10		
	Ensure t diagram	e that the mains supply is isolated before commencing installation and refer to the circuit im with the relevant product.		
Suitable and matches the Definity, Mode, Polar & Part M ranges	Suitable	Part M ranges		

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tarnworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com

