

Technical Specification



Product Code:	MD075SC		Description:	10A Ingot 3 Position Retra	active Switch Module	
	General Infor				BS EN BS EN BDB69-1 CLICK 1DAX 2507	
	Dimensio		25 (W) x 57 (H) x 27 (D)		
		Finish	Satin Chrome			
	Ν	/laterials	Terminal Screv	: Urea Stainless Steel vs: Steel & Yellow Passivated rs: Formed Pressed Brass	Rear Housing: Nyl Terminals: Brass d Contacts: Silver "o	on n-lay" Copper / Brass
	Rated Voltage (\	/~) (Ue)	250	Serie Sinte a Pressea Brass	Frequency (Hz)	50
Resistive Load Rating (A)		10				
Termination Type		Screw				
Terminal Size (mm)			Term	inal Torque Value (Nm)	0.5	
Terminal Capacity - Solid (mm ²)		· · /	4 x 1.5 or 2 x 2			
Modular Rocker Switches		Yes				
1 Pole 3 Position Switch		Yes				
Retractive Contact Options		Press to Make				
Minimum Back Box Depth (mm)		25 (35 Flat Pla	te)			
Operational Temperature (°C)		-5 to +40				
	Warranty	(Years)	10			
Additio	nal Information	Ensure tl diagram	hat the mains su with the relevan	of products, use only a soft, ipply is isolated before com t product. always be covered with appl	mencing installation and	

C E C K

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tarnworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com