

**Product Code:** OA502AG

**Description:** 2 Gang IP66 Weatherproof Unfurnished Unit



### General Information

<b>Dimensions (mm)</b>	158 (W) x 158 (H) x 90 (D)		
<b>Accessory Fixing Centres (mm)</b>	120.6		
<b>Finish</b>	Anthracite Grey		
<b>Gasket Colour</b>	Black		
<b>Materials</b>	Cover, Housing & Clip: Polycarbonate	Seal & Gasket: Rubber	
<b>Anti Microbial Certified</b>	No		
<b>Maximum Accessory Depth (mm)</b>	35		
<b>Back Box Knockouts - Total (mm)</b>	8 x Ø20		
<b>Back Box Knockouts - Top (mm)</b>	1 x Ø20	<b>Back Box Knockouts - Sides (mm)</b>	2 x Ø20
<b>Back Box Knockouts - Bottom (mm)</b>	2 x Ø20	<b>Back Box Knockouts - Rear (mm)</b>	1 x Ø20
<b>Ingress Protection</b>	IP66		
<b>Operational Temperature (°C)</b>	-5 to +40		
<b>Warranty (Years)</b>	5		

**Additional Information** For cleaning / polishing of products, use only a soft, dry, clean cloth.  
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.  
 Accepts standard two gang accessory plates.