## essentials™

Product Code: PRW210

## **Technical Specification**





## **General Information**

86 (W) x 86 (H) x 43 (D) Dimensions (mm)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Round Finish Polar White

Materials Cover & Pattress: Urea

Terminal Housing: Urea Neon Lens: Polycarbonate

Terminals: Brass Internal Busbars: Formed Pressed Brass

Terminal Screws: Steel & Yellow Passivated

Earth Strap: Mild Steel

Pull Bell: Urea

Anti Microbial Certified Yes

Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50

Resistive Load Rating (A) 45 Termination Type Screw

Terminal Size (mm) Ø6 Terminal Torque Value (Nm) 2.5

Terminal Capacity - Solid (mm<sup>2</sup>) 1 x 6

Double Pole Switch Twin Earth Terminals

Neon Indicator Indicator Colour Orange Yes

Mechanical Indicator Yes

Mechanical Indicator Type On/Off Rotating Legend

Minimum Back Box Depth (mm) Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years)

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of nonenveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.



