

Product Code: PSPSF247S

Technical Specification

Description: Powersaver Plus Electronic 24/7 Fused Boost controller with Programmable

Operations in Silver





General Information			
Dimensions (mm)		86 x 86 x 35	
Flush Mounting Back Box Depth (mm)		25	
Finish		Silver	
Displa	ay l	LCD, Clear Indication Display	
Materia	ls /	ABS	
Mountir	ıg S	Surface and Flush Mounting	
Warranty (Years)		3	
Programming			
Programming Schedule	24	24 Hour, 5/2 Day & 7 Day	
Available Operations	Up	Up to 10 per Day	
Summer/Winter Time Change	Ye	Yes (Automatic)	
Memory Reserve	Pe	Permanent Reserve Setting	
Button Lock	Yes		
Selectable Boost Durations		15 Minutes, 30 Minutes, 1 Hour, 2 Hours, 4 Hours, or 6 Hours	
Supply & Power			
Supply Voltage (V A	C)	230	
Frequency (H	z)	50	
Fuse Fitted (BS136	2)	13A	
Environment			
Ingress Protection	IP20		
Operating Temperature (°C)	0 to +40		

Outputs	
Switched Output	230V AC, Double Pole; Fused 13A Resistive (3kW)
Maximum LED Lamp Load Rating (W)	200 @ 230V
Maximum Incandescent, Halogen Lamp Load Rating (W)	750
Maximum Fluorescent Lamp Load Rating (W)	500
Maximum Fluorescent Lamp Load Rating (W)	500

Standards BS EN 60730

Temperature Rating T40

Supplied BS1362 13A Fuse





