



Type 2 , Single Phase, 1 Module SPDs

- Designed and tested for use with Lewden branded distribution boards
- Suitable for use in TN-C-S (PME) / TN-S / TT network systems
- Earth leakage free and may be connected before or after RCCB/RCBO circuit protection



SRGT2CU

| TECHNICAL DATA | | REGISTRY | |
|---------------------------------|---------------------|---------------------|------------------|
| Surge protective class | Type 2 | Net weight | 0.11KG |
| Rated operating voltage | 230V | Min order quantity | 1 |
| Frequency | 50-60Hz | EAN Code | 5026992040201 |
| Earthing Systems | TT | Gross Weight | 0.12KG |
| Earthing Systems | TN-C-S-(PME) | Dimensions | 90x18x67mm (HWD) |
| Earthing Systems | TN-S | | |
| Recommender backup MCB | 40A/50A B/C 6kA MCB | REFERENCE STANDARDS | STANDARDS |
| Nm dischar. current(In)(8/20uS) | 40kA (N/PE) | EN 61643-11:2012 | |
| Nm dischar. current(In)(8/20uS) | 20kA (L/N,L/PE) | IEC 61643-11:2011 | |
| Maximum discharge current | 50kA (L/N)" | | |
| Voltage protection level (Up) | <1,5kV (L/N) | | |
| Voltage protection level (Up) | <1,5kV (L/PE) | | |
| Voltage protection level (Up) | <1,5kV (N/PE) | | |
| Phase | 1 | | |
| Modules Number | 1 | | |
| Signalling contact | NO | | |
| Execution | DIN RAIL MOUNTING | | |