

Technical Specification



Product Code: VPAB152 Description: 2 Gang 2 Way 400Va Dimmer Switch





General Information

Plate Dimensions (mm) 88 (W) \times 88 (H) \times 8 (D) Dimensions With Gasket (mm) 91 (W) \times 91 (H) \times 9 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

Style Victorian
Finish Antique Brass

Gasket Colour Black

Materials Front Plate & Control Button: Stainless Steel Rear Housing: Nylon

Terminals: Brass Terminal Screws: Steel & Yellow Passivated

PCB: Mixed Components Earth Strap: Mild Steel

Gasket: Nylon

Anti Microbial Certified No

Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50/60

Load Rating (W) 60 - 400

Load Rating Comments Suitable For Resistive / Inductive Loads

Termination Type Screw

Terminal Size (mm) Ø3.5 Terminal Torque Value (Nm) 0.4

Terminal Capacity - Solid (mm²) 2 x 1.5 2 Way Switch Yes

Switch Control Type Press - ON/OFF, Rotate - Dim

Dimmer Technology Type Leading Edge

Dimmer Load Type Resistive & Inductive

Minimum Back Box Depth (mm) 25 Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 10 Warranty - Electronics (Years) 1

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Compatible Dimmer Modules MD9014: 100W Dual Mode LED Dimmer Module

MD9001: 6A Push ON/OFF (Dummy Dimmer / Non Dimmable) Module

MD9010: 1-10V Analogue Rotary Dimmer Module MD9022: 40-250W Leading Edge Dimmer Module



E: sales@scolmore.com | W: scolmore.com