

Technical Specification



Product Code: VPAB535BK **Description:** 13A Ingot 1 Gang Double Pole Switched Socket Outlet





General Information

Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D) Dimensions With Gasket (mm) 91 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Victorian Finish Antique Brass

Insert Colour Black Gasket Colour Black

Materials Front Plate: Stainless Steel Insert & Housing: Urea Switch Cover: Stainless Steel Terminals: Brass

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Gasket: Nylon

Frequency (Hz) 50

Terminal Torque Value (Nm) 2

Earth Strap: Mild Steel

Contacts: Silver "on-lay" Copper / Brass

Rated Voltage (V~) (Ue) 250 Resistive Load Rating (A) 13

Anti Microbial Certified

Termination Type Screw

Terminal Size (mm) Ø5

No

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Double Pole Switch Yes Minimum Back Box Depth (mm) 25

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years)

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

