

Technical Specification



Product Code: VPAB550BK

Description: 13A Ingot Fused Connection Unit With Optional Flex Outlet



General Information

General mormation			
Plate Dimensions (mm)	88 (W) x 88 (H) x 8 (D)		
Dimensions With Gasket (mm)	91 (W) × 91 (H) × 9 (D)		
Plate Fixing Centres - Horizontal (mm)	60.3		
Style	Victorian		
Finish	Antique Brass		
Insert Colour	Black		
Gasket Colour	Black		
Materials	Front Plate: Stainless Steel	Insert & Housing: Urea	
	Fuse Drawer Cover: Stainless Steel	Terminals: Brass	
	Terminal Screws: Steel & Yellow Passivated	Internal Busbars: Formed Pressed Brass	
	Earth Strap: Mild Steel	Gasket: Nylon	
Anti Microbial Certified	No		
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50	
Resistive Load Rating (A)	13		
Fuse Fitted Rating & Type	13A (BS 1362)		
Termination Type	Screw		
Terminal Size (mm)	Ø5 Termina	Il Torque Value (Nm) 2	
Terminal Capacity - Solid (mm ²)	3 x 2.5 or 2 x 4		
Switched	No		
Twin Earth Terminals	Yes		
Product Marking	Fused		
Flex Outlet Available	Yes		
Flex Outlet Location	Front of Plate Flex Out	tlet Dimension (mm) Ø10	
Minimum Back Box Depth (mm)	25		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10		
Ensure t diagram	or cleaning / polishing of products, use only a soft, dry, clean cloth. nsure that the mains supply is isolated before commencing installation and refer to the circuit agram with the relevant product. are earth cables must always be covered with appropriate sleeving and wired to the earth terminal.		
, , , , , , , , , , , , , , , , , , , ,			