

Technical Specification



Product Code: VPAB752BK Description: 13A Ingot Double Pole Switched Fused Connection Unit With Neon





General Information

Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D) Dimensions With Gasket (mm) 91 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Victorian Finish Antique Brass

> > 250

Insert Colour Black Gasket Colour Black

> Materials Front Plate: Stainless Steel

> > Switch & Fuse Drawer Cover: Stainless Steel

Terminals: Brass Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

Frequency (Hz) 50

Gasket: Nylon

Insert & Housing: Urea

Neon Lens: Polycarbonate

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Resistive Load Rating (A) 13

Fuse Fitted Rating & Type 13A (BS 1362)

> Termination Type Screw

Terminal Size (mm) Terminal Torque Value (Nm) 2 05

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Anti Microbial Certified Rated Voltage (V~) (Ue)

> Switched Yes Double Pole Switch Yes

Twin Earth Terminals Yes

Neon Indicator Yes Indicator Colour Red

Product Marking Fused

Minimum Back Box Depth (mm) 25

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

