

## **Technical Specification**

Product Code: VPBN065BK Description: Single Non-Isolated Coaxial Outlet





Insert: Urea

Earth Plate: Mild Steel

## **General Information**

Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D) Dimensions With Gasket (mm) 91 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Victorian Finish Black Nickel

Insert Colour Black Gasket Colour Black

Materials Front Plate: Stainless Steel

Terminals: Brass Gasket: Nylon

Anti Microbial Certified No

Termination Type Screw

Isolated No Non-Isolated Yes

Shielded No

Minimum Back Box Depth (mm) 16

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years)

## **Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Isolated socket will filter out any interference, if a 2 way signal is required, i.e. for use with satellite hard

wire extensions, then a non-isolated outlet is required.