


## **Technical Specification**

Product Code: VPSC504BK

**Description:** 45A Ingot 2 Gang Double Pole Switch With 13A Double Pole Switched





Insert & Rear Housing: Urea

Gasket: Nylon

Terminal Torque Value (Nm) 2.5

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

## **General Information**

Plate Dimensions (mm) 146 (W) x 88 (H) x 8 (D) Dimensions With Gasket (mm) 149 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm)

Style Victorian Finish Satin Chrome

Insert Colour Black Gasket Colour

Materials Front Plate: Stainless Steel

> Terminals: Brass Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

No

Anti Microbial Certified Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50

Resistive Load Rating (A) 45 Termination Type Screw Terminal Size (mm) 016

1 x 16

Terminal Capacity - Solid (mm<sup>2</sup>) Double Pole Switch Yes

Twin Earth Terminals Yes

Product Marking On, Off, Socket, Cooker

Minimum Back Box Depth (mm) 35

Ingress Protection IP20 Operational Temperature (°C) -5 to +40

Warranty (Years)

For cleaning / polishing of products, use only a soft, dry, clean cloth. **Additional Information** 

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

