## essentials<sup>™</sup>

## **Technical Specification**



## Product Code: WARCDP036

Description: 13A 2 Gang Type A Passive RCD Switched Socket Outlet



## **General Information**

Plate Dimensions (mm)	146 (W) x 86 (H) x 9.5 (D)	
Plate Fixing Centres - Horizontal (mm)	120.6	
Style	Rounded Profile	
Finish	Essentials White	
Materials	Front Plate & Rocker Switch: Urea	Rear Housing: Urea
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated
	Contacts: Silver "on-lay" Copper / Brass	Internal Busbars: Formed Pressed Brass
	Earth Strap: Mild Steel	PCB: Mixed Components
Anti Microbial Certified	Yes	
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Resistive Load Rating (A)	13	
Breaking Capacity (A)	250 (Earth Leakage)	
Through Fault Withstand (A)	1500	
Trip Speed	Less than 40ms at 150mA Residual Current	
Termination Type	Screw	
Terminal Size (mm)	Ø5 Termin	al Torque Value (Nm) 2
Terminal Capacity - Solid (mm <sup>2</sup> )	3 x 2.5 or 3 x 4	
Single Pole Switched	Yes	
Twin Earth Terminals	Yes	
Minimum Back Box Depth (mm)	35	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	
Additional InformationFor cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses. All products have been independently tested with 99.9% of enveloped viruses and 92% of non- enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.		

UK CA

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tarnworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com

Page 1 of 1 (20/02/22) Errors & Omissions excluded. Specification is subject to change without notice.